

## SPL 1800c1



### Specifications:

Channels	no	<b>1</b>
Class	Typ	<b>D</b>
Power @14,4V /3.0% THD		
@ 4 ohm:	Wrms	<b>965</b>
@ 2 ohm:	Wrms	<b>1760</b>
@ 1 ohm:	Wrms	<b>1760</b>
Operation supply	V	<b>10 -16</b>
Thermal protection	°C	<b>80</b>
THD @ 4 Ω / 50% Pmax	%	<b>0,2</b>
Signal/noise	dB	<b>84</b>
Efficiency	%	<b>89</b>
Input sensitivity	Vrms	<b>0,2-8</b>
Low input impedance	Ω	<b>10 k</b>
Damping @ 80 Hz		<b>302</b>
Power consumption, idle	A	<b>2</b>
Power cons. 2 Ω	A	<b>75</b>
Power cons. 4 Ω	A	<b>138</b>
Weight	kg	<b>5,8</b>
Dimensions	l/w/h	<b>424/180/58 mm</b>

### Features:

- Lowpass filter with 24 dB dB slope.
- Subsonic filter
- Phase shift 0 - 180°
- Bass adjust 0 – 12 dB
- Optional remote available

### Miscellaneous:

- Protection for overhead, over current, short circuitry and speaker DC protection
- Massive heavy aluminum-heat sink with intelligent fan cooling